### จอภาพแบบสัมผัสเกรดอุตสาหกรรม

## **Industrial Touch Monitor**





Model: CPT-170M-BBC1151

#### Introduction

This industrial-grade touch screen is a rugged human-computer interaction device with an aluminum alloy structure and low power consumption. With its stable performance, it performs well in industrial applications. The design of the whole machine focuses on reliability, environmental adaptability, scalability, compatibility, etc. It is widely used in smart production workshops, industrial control equipment, mechanical equipment, power cabinets, visual inspection equipment, artificial intelligence, commercial terminals, ship-mounted vehicles, smart medical care, smart transportation and other fields.

#### **Specifications**

Screen size	17 inch LCD
Resolution	1280x1024
Brightness	400 cd/m2
Screen touch type	10-point touch projection Single-point Capacitive touch screen
clicks	capacitive > 50 million times
Surface hardness	>7H
Touch strength	45g
Glass type	Chemically enhanced plexiglass
Color	16.7M
Contrast ratio	1000:1
Viewing angle	85/85/85/85 (L/R/U/D)
Anti-interference	EMC EMI
Anti-vibration	GB242 standard
VLT	>85%
	Resolution Brightness Screen touch type clicks Surface hardness Touch strength Glass type Color Contrast ratio Viewing angle Anti-interference Anti-vibration

# งวภาพแบบสัมผัสเกรดอุตสาหกรรม Industrial Touch Monitor CPT-170M-BBC1151

	1+00
•	1*DC
VGA	1*VGA
HDMI	1*HDMI
DP	1*DP
DVI	1*DVI
Touch	1*USB Touch connector
Audio	1*PC AUDIO (3.5mm)
MTBF Time	50000 Hours
Temperature/Humidity	Working temperature: 0~60°C; Storage temperature: -10~70°C; humidity: 10~95% non-condensing
IP Grade	Front panel IP65 dust and water resistant
Shell material	Aluminum alloy shell
Shell color	Black
Power adapter	AC100V~240V、50Hz/60Hz Input DC 12V
Installation methods	Support wall hanging/desktop/cantilever
Warranty	12 Months 24 Months (Optional)
Product weight	4.7KG
1PCS Package weight	8.5KG
Product size	418*350*66mm(L*W*T)
Embedded hole size	398*330mm (Please reserve an extra 1-2mm error for the opening the hole)
Packing item	Power adapter*1, Power cable*1, Embedded buckle*4, Screws*4
Certificate	CE/FCC Certificates
	DP DVI Touch Audio MTBF Time  Temperature/Humidity  IP Grade Shell material Shell color Power adapter Installation methods  Warranty  Product weight 1PCS Package weight Product size  Embedded hole size  Packing item



